



1 1/4" 848R Quick Opening Throttle-Type Gate Valve

FOR PETROLEUM ONLY



Non-Potable Use Only

1. On some models, a circular tag is attached to the cap.
READ THE INFORMATION ON THIS TAG.
2. Valve **MUST** be installed in horizontal pipe lines with cap pointing upward. Installations in vertical pipelines are **NOT** to be made.
3. Precautions should be taken to make sure line fluid is free of grit or abrasive material as they will damage the sealing surfaces and cause leakage.
4. Valve is intended for use with hydraulic or oil based fluids **ONLY. DO NOT USE WITH WATER.** Certain chemicals can be harmful to the rubber seals. If chemicals are present and can contact rubber seals consult with manufacturer on acceptability.
5. Unless otherwise indicated, valve is intended for 250 PSIG non-shock, ambient or cold temperature working pressure. Contact factory before using at higher pressures.

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.



1 1/4" 848R Quick Opening Throttle-Type Gate Valve

FOR PETROLEUM ONLY



Non-Potable Use Only

1. On some models, a circular tag is attached to the cap.
READ THE INFORMATION ON THIS TAG.
2. Valve **MUST** be installed in horizontal pipe lines with cap pointing upward. Installations in vertical pipelines are **NOT** to be made.
3. Precautions should be taken to make sure line fluid is free of grit or abrasive material as they will damage the sealing surfaces and cause leakage.
4. Valve is intended for use with hydraulic or oil based fluids **ONLY. DO NOT USE WITH WATER.** Certain chemicals can be harmful to the rubber seals. If chemicals are present and can contact rubber seals consult with manufacturer on acceptability.
5. Unless otherwise indicated, valve is intended for 250 PSIG non-shock, ambient or cold temperature working pressure. Contact factory before using at higher pressures.

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.



1 1/4" 848R Quick Opening Throttle-Type Gate Valve

FOR PETROLEUM ONLY



Non-Potable Use Only

1. On some models, a circular tag is attached to the cap.
READ THE INFORMATION ON THIS TAG.
2. Valve **MUST** be installed in horizontal pipe lines with cap pointing upward. Installations in vertical pipelines are **NOT** to be made.
3. Precautions should be taken to make sure line fluid is free of grit or abrasive material as they will damage the sealing surfaces and cause leakage.
4. Valve is intended for use with hydraulic or oil based fluids **ONLY. DO NOT USE WITH WATER.** Certain chemicals can be harmful to the rubber seals. If chemicals are present and can contact rubber seals consult with manufacturer on acceptability.
5. Unless otherwise indicated, valve is intended for 250 PSIG non-shock, ambient or cold temperature working pressure. Contact factory before using at higher pressures.

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.



1 1/4" 848R Quick Opening Throttle-Type Gate Valve

FOR PETROLEUM ONLY



Non-Potable Use Only

1. On some models, a circular tag is attached to the cap.
READ THE INFORMATION ON THIS TAG.
2. Valve **MUST** be installed in horizontal pipe lines with cap pointing upward. Installations in vertical pipelines are **NOT** to be made.
3. Precautions should be taken to make sure line fluid is free of grit or abrasive material as they will damage the sealing surfaces and cause leakage.
4. Valve is intended for use with hydraulic or oil based fluids **ONLY. DO NOT USE WITH WATER.** Certain chemicals can be harmful to the rubber seals. If chemicals are present and can contact rubber seals consult with manufacturer on acceptability.
5. Unless otherwise indicated, valve is intended for 250 PSIG non-shock, ambient or cold temperature working pressure. Contact factory before using at higher pressures.

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.